Intended Use

This high performance retrofit kit system is an ideal upgrade solution for existing strip light fixtures. Delivers bright and clear lighting for warehouses, work areas, retail stores and offices.

Features

- · Designed to cover over existing standard linear strip light fixture with easy to install system
- Standard commercial grade cover with clean cut frame provides a new look to the existing fixture
- Integrated 0 10V dimming
- Aluminum PCB with high thermal conductivity as chip carrier for faster cooling
- Low profile design meets ADA requirements

Listings

- Conforms to UL 1598
- DesignLights Consortium®qualified product
- Suitable for damp location

Warranty / Life

- 5 Years
- 50,000 Hours



PRODUCT SPECIFICATIONS

	Reference	1 1 1	Wattage	1	Voltage	1 1 1	Lumens	 - -	Color Temp	1	CRI	 - -	IP	1	Dimmable	1 1	Photo Sensor	 	THD I	Operating Temp	1	Warranty	 	Certification	 	DLC/ES
ı		1		ı		ı		ı		ı		ı		ı		ı		ı	- 1		1		ı		ı	- 1
ı	L22-01	1	25W	T	120-277V	T	3,250	L	3,000K	ı	80	ı	44	ī	Yes	ı	No	1	<20% ▮	4F to 104F	1	5 Years	1	UL	1	Yes
1	L22-02	1	25W	Ţ	120-277V	L	3,250	ı	4,000K	ļ	80	ı	44	ı	Yes	I	No		<20% I	4F to 104F	1	5 Years	I	UL	1	Yes
	L22-03	:	25W	t	120-277V	t	3,250	:	5,000K	:	80		44	t	Yes	t	No	!	<20%	4F to 104F	1	5 Years	:	UL	!	Yes
- [L22-04	ŀ	40W	ŀ	120-277V	ŀ	4,700	!	3,000K	ŀ	80		44	ŀ	Yes	ŀ	No		<18%	4F to 104F	i	5 Years	1	UL	ŀ	Yes
i	L22-05	i	40W	i	120-277V	Ĺ	4,853	i	4,000K	i	80	i	44	i	Yes	i	No	i i	<18%	4F to 104F	i	5 Years	i	UL	Ĺ	Yes
i	L22-06	ī	40W	ı	120-277V	ı	4,505	ı	5,000K	ı	80	ı	44	ı	Yes	ı	No	ı ·	<18%	4F to 104F	ī	5 Years	ı	UL	1	Yes

DIMENSIONS

