

## PRODUCT INFORMATION

## Bi-Directional Wall Pack

### Intended Use

The clean cut-off design distributes an attractive bi-directional up and down pattern of light. For use in entryways and building periphery.

### Features

- LEDs deliver an expected service life of more than 50,000 hours and eliminate frequent lamp changes associated with traditional sources
- Aluminum faceplate offers supreme durability and heat dissipation from LED and power supply
- Top and bottom glass lens design allows for clear evenly distributed lights on both ends

### Listings

- Conforms to UL 1598
- Energystar® qualified product
- IP 65 rated

### Warranty / Life

- 5 Years
- 50,000 Hours



## PRODUCT SPECIFICATIONS

Reference	Wattage	Voltage	Lumens	Color Temp	CRI	IP	Dimmable	Photo Sensor	THD	Operating Temp	Warranty	Certification	DLC/ES
L08-01	24W	120V	1,880	3,000K	80	65	No	No	<20%	-4F to 104F	5 Years	ETL	Yes
L08-02	24W	120V	1,880	4,000K	80	65	No	No	<20%	-4F to 104F	5 Years	ETL	Yes
L08-03	24W	120V	1,880	5,000K	80	65	No	No	<20%	-4F to 104F	5 Years	ETL	Yes

## DIMENSIONS

